



Ultramax Brake Fluid DOT 4

Synthetic fluid to DOT 4 specifications

Product code: H053

Product Description:

Ultramax Brake Fluid DOT 4 is manufactured from specialised synthetic components under strict conditions to produce a high quality brake & clutch fluid with a very high operating temperature. Ultramax Brake Fluid DOT 4 is specially formulated for use in the majority of automotive applications, however it is recommended that the user should always check in the vehicle handbook before use.

Benefits:

- Suitable for use in a wide variety of systems where a non-mineral oil based fluid is recommended
- Meets DOT 4 specification for improved heavy braking performance
- Mixes with DOT 3 brake fluids
- Has a high boiling point ensuring excellent performance even under arduous conditions

Applications:

Ultramax Brake Fluid DOT 4 is suitable as a brake and clutch fluid for a wide variety of cars, commercial vehicles and motorcycles.

Product Specification:

US FM VSS 116 DOT 4
US FM VSS 116 DOT 3
SAE J1703, J1704
ISO 4925 (Classes 3 & 4)

Typical Characteristics

| | |
|---------------------------------------|-------------|
| Appearance | Pale Yellow |
| Specific Gravity @ 15.6 °C | 1.040 |
| Kinematic Viscosity @ 100 °C (cSt) | 2.17 |
| Equilibrium Reflux Boiling Point (°C) | 243 |
| Wet Equilibrium Boiling Point (°C) | 159 |
| Kinematic Viscosity @ -40 °C (cSt) | 1296 |
| pH | 8.3 |

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.