



Optifarm Ultra 15W-40

Mineral oil based super universal tractor oil

Product code: M240

Product Description:

Optifarm Ultra 15W-40 is an advanced high performance universal oil designed for use in the latest agricultural machinery. It is also recommended for a number of other off-highway equipment including construction, demolition and excavation where any of the specifications below and a SAE 15W-40 viscosity grade are called for.

Optifarm Ultra 15W-40 is formulated using highly refined mineral base stocks together with state of the art additives which provide high performance in engine, transmission hydraulics, axles, wet-brakes the ultimate protection against wear and corrosion and help eliminate wet brake noise and chatter.

Benefits:

- Exceptional wear protection
- Enhanced anti-squawk properties providing superior wet brake performance
- Improved low temperature stability
- Meets a variety of OEM requirements
- Suitable for a wide range of off highway machinery requirements
- High API diesel specification

Applications:

Optifarm Ultra 15W-40 is suitable for use in naturally aspirated and turbocharged diesel and petrol engines, transmissions, hydraulic systems, final drives, wet brakes and oil immersed clutches.

Performance Specification

STOU Specifications

Massey Ferguson	M1145
	M1144
New Holland	NH024C
John Deere	J27
ZF	TE-ML 03A
	TE-ML 06B, 06C,
	TE-ML 07B, 07D



UTTO Specifications

Massey Ferguson	M1145 M1143
Ford	M2C134-D

Gear & Transmission Specifications

API	GL-4
AGCO	CVT ML 200
Allison	C4
Caterpillar	TO-2
Afnor	NFE 68603 E

Engine Specifications

ACEA	E3
API	CG-4, CF-4, CF, CE/SF
MB	227.1, 228.1
MAN	271
Ford	M2C121-B
CCMC	D4
Military	MIL-L-2104D

Typical Test Data

Specific Gravity @ 15.6°C	0.886
Kinematic Viscosity @ 100°C (cSt)	13.35
Flash Point COC (°C)	225
Pour Point (°C)	-35
TBN (mg KOH / g)	10.45

Health and Safety

Please refer to the safety data sheet, a copy of which is freely available to all our customers.