



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Taurus SHPD E3 15W-40



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Taurus SHPD E3 15W-40

Mineral oil based heavy duty diesel engine oil.

Product code: M097

Product Description:

Taurus SHPD E3 15W-40 is a super high performance multigrade diesel engine oil meeting many OEM long drain requirements. It offers extended drain periods of up to 60,000 km depending upon operating conditions and reduces unwanted sludge and varnishes in cylinders, valves and on pistons in highly stressed diesel engines.

Benefits

- Extended drain of up to 60,000 kilometres
- Lower maintenance costs
- Prevents bore polishing
- Outstanding corrosion protection

Applications:

Taurus SHPD E3 15W-40 is suitable for normally aspirated and turbocharged highly rated diesel engines in trucks, buses, coaches, plant and industrial equipment. It is miscible with all synthetic and mineral based oils.

Product Specification:

API	CH-4/SL, CF
ACEA	A3/B3,A3/B4,E3
MB	229.1, 228.3
Mack	EO-L
MAN	M 3275
Volvo	VDS-2
Renault	RVI RD
MTU	Type 2

Typical Test Data:

Specific Gravity @ 15.6°C	0.888
Kinematic Viscosity @ 100°C (cSt)	14.59
Kinematic Viscosity @ 40°C (cSt)	109.02
Viscosity Index	138
Flash Point COC (°C)	215
Pour Point (°C)	-29
TBN (mg KOH / g)	10.65

Health and Safety:

Please refer to the relevant safety data sheet, a copy of which is freely available to all our customers.