



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Victory 15W-40



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Victory 15W-40

Mineral oil based engine oil

Product code: M016

Product Description:

Victory 15W-40 is a mixed fleet, multigrade engine oil. Victory 15W-40 is manufactured from highly refined, high viscosity index base oils and carefully balanced mixed fleet additives producing a high quality petrol and diesel engine oil. It offers excellent high temperature stability and stay in grade performance.

Benefits:

Good passenger car and light commercial performance
Stay in grade performance
Cost effective
Good anti-wear properties

Applications:

Victory 15W-40 is suitable for normally aspirated and turbocharged diesel engines and petrol engines in passenger cars and light commercials. It is miscible with all synthetic and mineral based engine oils.

Product Specification:

| | |
|---------------|-------------|
| API | CD/SF |
| CCMC | G2/D2 |
| Caterpillar | Series 3 |
| Allison | C-3 |
| Military Spec | Mil-L-2104C |

Typical Test Data:

| | |
|-----------------------------------|--------|
| Specific Gravity @ 15.6°C | 0.884 |
| Kinematic Viscosity @ 100°C (cSt) | 14.67 |
| Kinematic Viscosity @ 40°C (cSt) | 112.04 |
| Viscosity Index | 135 |
| Flash Point COC (°C) | 217 |
| Pour Point (°C) | -28 |
| TBN (mg KOH / g) | 6.51 |

Health and Safety:

Please refer to the relevant safety data sheet, a copy of which is freely available to all our customers.