



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Micron BR MP & MO Grades



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Micron BR MP & MO Grades

Mineral oils with special requirements

Product code: See table below

Product Description:

Micron BR, MP and MO grades are manufactured to comply with the British Rail Specification 663.

Micron BR, MP and MO grades are blended from solvent refined base oils of high thermal and chemical stability and fortified with pour point depressants to achieve the standards required in the 663 specification.

Benefits:

- Cost effective
- Wide range of applications

Application:

Recommended for use in the rail industry where the original British Rail Specification 663 is required.

Typical Test Data:

Micron BR M Grade	MP 46	MO 68	MO 100	MO 150
Product Code	L022	L023	L024	L025
Specific Gravity @ 15.6°C	0.878	0.882	0.888	0.891
Kinematic Viscosity @ 100°C (cSt)	6.8	8.8	11.4	15.1
Kinematic Viscosity @ 40°C (cSt)	46.0	68.0	100.0	150.0
Viscosity Index	102	101	101	101
Flash Point (COC, °C)	220	225	228	231
Pour Point (°C)	- 12	- 12	- 12	- 11

Health & Safety:

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.