



**EXCELLENCE IN LUBRICANTS**

## *TECHNICAL DATA SHEET*

Taurus 30



**EXOL LUBRICANTS LIMITED**

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

[WWW.EXOL-LUBRICANTS.COM](http://WWW.EXOL-LUBRICANTS.COM)



# Taurus 30

Mineral oil based monograde engine oil

Product code: M048

## Product Description:

Taurus 30 engine oil is a superior quality monograde lubricant. The combination of solvent refined base oils and high technology additives is designed to give maximum protection to engines working under moderate to severe conditions. The state of the art additives prevent build up of carbon and lacquer deposits on piston ring grooves and valve stems and dramatically reduce the corrosive effects of the products of combustion.

## Benefits:

Excellent high temperature stability  
Improved bore polishing protection  
Excellent anti wear performance for reduced engine wear  
Excellent sludge control

## Applications:

Taurus 30 may be used in a variety of turbocharged and naturally aspirated diesel engines where a monograde SAE 30 lubricant is specified. Typical applications are earth movers, general plant equipment, large and small trucks, vans and taxis. This product may also be suitable for use in plant equipment hydraulic systems, transmissions and torque converters. Refer to manufacturer's handbook.

## Product Specification:

API	CE/SG
Military	Mil-L-46152B Mil-L-2104D
CCMC	D4
MB	227.0, 227.1
Mack	EO-K
MAN	270, 271
Caterpillar	TO-2
Allison	C3



## TECHNICAL DATA SHEET

### Typical Test Data:

Specific Gravity @ 15.6°C	0.884
Kinematic Viscosity @ 100°C (cSt)	11.66
Kinematic Viscosity @ 40°C (cSt)	99.91
Viscosity Index	105
Flash Point COC (°C)	220
Pour Point (°C)	-30
TBN (mg KOH / g)	9.20

### Health and Safety:

Please refer to the relevant safety data sheet, a copy of which is freely available to all our customers.