

# TECHNICAL DATA SHEET

Performance Plus 15W-40



### **EXOL LUBRICANTS LIMITED**

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM





## **Performance Plus 15W-40**

Mineral oil based engine oil

**Product code: M023** 

#### **Product Description:**

Performance Plus 15W-40 is a multigrade engine oil manufactured from highly refined, high viscosity index base oils and carefully balanced additives producing a high quality petrol and diesel engine oil. It offers excellent high temperature stability and stay in grade performance. The additives used reduce the unwanted gums and varnishes in cylinders, on pistons and in turbochargers.

#### **Benefits:**

- Excellent performance
- Protection against sludging
- Stay in grade performance
- Good anti wear properties

#### **Applications:**

Performance Plus 15W-40 is suitable for normally aspirated and turbo charged diesel engines and petrol engines in passenger cars, light and heavy commercials, buses, agricultural, plant and construction equipment. It is miscible with all synthetic and mineral based engine oils.

#### **Product Specification:**

| API           | SG/CF-4     |
|---------------|-------------|
| Caterpillar   | TO-2        |
| CCMC          | G3/PD-2     |
| VW            | 505.00      |
| MB            | 227.1       |
| MAN           | 271         |
| Allison       | C3          |
| Military Spec | Mil-L-2104E |

#### **Typical Test Data:**

| Specific Gravity @ 15.6°C         | 0.886 |
|-----------------------------------|-------|
| Kinematic Viscosity @ 100°C (cSt) | 14.3  |
| Kinematic Viscosity @ 40°C (cSt)  | 105.0 |
| Viscosity Index                   | 139   |
| Flash Point COC (°C)              | 215   |
| Pour Point (°C)                   | -29   |
| TBN (mg KOH / g)                  | 9.09  |

#### **Health & Safety:**

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.