



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Excelguard WD



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Excelguard WD

Solvent deposited, water displacing rust preventative

Product code: R036

Product Description:

Excelguard WD is a solvent deposited water displacing corrosion preventative.

Excelguard WD is a blend of dewatering agents, corrosion inhibitors, hydrocarbon mineral oils, waxes, synthetic sulphonates and hydrocarbon solvents. It offers medium term protection of ferrous and aluminium alloy components. It leaves a light oily film when applied.

Benefits:

- Solvent deposited
- Excellent dewatering properties

Application:

Excelguard WD is best applied by dipping, spraying or brushing. If a tank is being used the residual water should be drained off periodically. Allow up to 40 minutes drying time. It may affect some rubbers and plastics on long term exposure.

Product Specification:

Protection Indoors	6 - 12 months
Protection Outdoors (covered)	3 months min.
Protection Outdoors	1 month
Film Thickness	2.1 microns
Covering Capacity	55 m ² /litre

Typical Test Data:

Specific Gravity @ 15.6°C	0.810
Kinematic Viscosity @ 40°C (cSt)	1.91
Film Type	Thin oily
Odour	Solvent

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.