



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Excelguard 507



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Excelguard 507

Solvent deposited, water displacing rust preventative

Product code: R007

Product Description:

Excelguard 507 is a solvent deposited water displacing corrosion preventative.

Excelguard 507 is a blend of de-watering agents, corrosion inhibitors, hydrocarbon mineral oils, synthetic sulphonates and hydrocarbon solvents. It offers long term protection of ferrous and aluminium alloy components. It leaves a thick resilient oily anti-corrosion film when applied. It is ideally suited to long inter-process protection after machining.

Benefits:

Solvent deposited
Excellent dewatering properties

Application:

Excelguard 507 is best applied by dipping, spraying or brushing. If a tank is being used the residual water should be drained off periodically. Allow up to 50 minutes drying time. It may affect some rubbers and plastics on long-term exposure.

Product Specification:

Protection Indoors	2 years +
Protection Outdoors (covered)	12 - 15 months
Protection Outdoors	9 months
Film Thickness	5 - 6 microns
Covering Capacity	52 m ² /litre

Typical Test Data:

Specific Gravity @ 15.6°C	0.851
Kinematic Viscosity @ 40°C (cSt)	5.74
Film Type	Semi-dry, stiff
Odour	Solvent

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.