



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Endurance 15W-40



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Endurance 15W-40

Mineral oil based engine oil

Product code: M330

Product Description:

Endurance 15W-40 has been designed to meet the specification requirements of the latest turbocharged and naturally aspirated diesel and petrol engines. Endurance 15W-40 is manufactured from heat stable, high viscosity index, solvent refined base oils with a balance of anti-oxidant, anti-wear, detergent and dispersant additives along with a shear stable viscosity improver ensuring easier starting and extended engine life.

Benefits:

- High shear stability for stay in grade performance
- Excellent high temperature stability
- Improved bore polishing protection
- Excellent anti-wear performance for reduced engine wear
- Ideal mixed fleet lubricant
- Excellent sludge control for stop-go city motoring

Applications:

Endurance 15W-40 is recommended for use in transport fleets, public service vehicles, plant equipment, light to heavy duty commercial vehicles and passenger cars.

Product Specification:

API	CG-4/SJ
ACEA	A3,B2,B3, E2
VW	501, 505
MB	228.1, 229.1
Mack	EO-M
MAN	271
MTU	Category 1
Volvo	VDS

Typical Test Data:

Specific Gravity @ 15.6°C	0.885
Kinematic Viscosity @ 100°C (cSt)	14.49
Kinematic Viscosity @ 40°C (cSt)	106.98
Viscosity Index	139
Flash Point COC (°C)	217
Pour Point (°C)	-30
TBN (mg KOH / g)	8.22



TECHNICAL DATA SHEET

Health & Safety:

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.