



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Excelform 2235



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Excelform 2235

High extreme pressure metal forming oil

Product code: F044

Product Description:

Excelform 2235 is a metal forming lubricant based on high viscosity mineral oils fortified with high levels of extreme pressure and lubricity additives.

Benefits:

- Very high film strength
- Can be applied by pump, spray, brush, or swab
- Excellent surface finish
- Prolonged tool and die life

Application:

Excelform 2235 has been designed for use on the most severe metal forming operations including cold heading, metal forming and blanking. This product is suitable for use with ferrous metals. Prolonged contact with non-ferrous materials should be avoided as this could induce staining.

Typical Test Data:

| | |
|----------------------------------|------------------|
| Specific Gravity @ 20°C | 0.983 |
| Kinematic Viscosity @ 40°C (cSt) | 105.5 |
| Flash Point COC (°C) | >220 |
| Colour | Dark amber |
| Appearance | Clear and bright |

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.