



# **Optiguard 10W-40**

Mineral oil based engine oil Product code: M102

#### **Product Description:**

High performance multigrade engine oil with multifleet applications. Optiguard 10W-40 is a multigrade engine oil manufactured from carefully selected base oils and additive technology. It meets many engine requirements and specifications. It can be supplied for mixed fleet applications. Superior dispersant additives help maintain engine cleanliness in petrol engines and the detergent additives help reduce unwanted deposits in turbochargers and on pistons.

#### **Benefits:**

- High shear stability for stay in grade performance
- · Excellent high temperature stability
- Improved bore polishing protection
- Excellent anti wear performance for reduced engine wear
- Ideal mixed fleet lubricant

#### **Applications:**

Optiguard 10W-40 is suitable for normally aspirated and turbocharged highly stressed petrol engines and diesel engines in the passenger cars and heavy commercials, vans, plant, buses and industrial equipment. It is miscible with all synthetic and mineral based engine oils.

# **Product Specification:**

| API   | SL/CH-4          |
|-------|------------------|
| ACEA  | A3/B3, A3/B4, E2 |
| VW    | 505.00           |
| MB    | 229.1            |
| Mack  | EO-L             |
| MAN   | 271              |
| MTU   | Type 1           |
| Volvo | VDS              |





### **Typical Test Data:**

| Specific Gravity @ 15.6°C         | 0.884 |
|-----------------------------------|-------|
| Kinematic Viscosity @ 100°C (cSt) | 13.82 |
| Kinematic Viscosity @ 40°C (cSt)  | 95.51 |
| Viscosity Index                   | 147   |
| Flash Point COC (°C)              | 212   |
| Pour Point (°C)                   | -32   |
| TBN (mg KOH / g)                  | 10.2  |

## **Health and Safety:**

Please refer to the relevant safety data sheet, a copy of which is freely available to all our customers.