



# Taurus GEO MAG 240

Premium medium ash gas engine oil

Product code: M475

## Product Description:

Taurus GEO MAG 240 is formulated from ultra pure base oils and the latest in medium ash additive technology which provides excellent control of deposit formation thereby preventing problems such as valve torching and piston ring and groove deposits.

The characteristics of Taurus GEO MAG 240 make it a perfect choice for engines running on sour gas, such as digester gas, sewage gas or landfill gas, where its acid neutralisation properties are required.

## Benefits:

- Extended oil life
- Excellent base number retention
- Outstanding deposit control on pistons and valves
- Optimised ash level
- Excellent anti-wear protection

## Applications:

Taurus GEO MAG 240 is recommended for use in applications requiring a medium ash gas engine oil such as engines running on aggressive gases, e.g. sewage gas, landfill gas or digester gas. In particular Taurus GEO MAG 240 is recommended in the following applications:

|              |   |
|--------------|---|
| GE-Jenbacher | Engine Types 2, 3, 4 & 6 (except 4C & 6F) |
| MAN          | 3271-4                                    |
| MWM          | >0.5% sulphated ash applications          |

## Typical Test Data:

|                                   |       |
|-----------------------------------|-------|
| SAE Grade                         | 40    |
| Specific Gravity @ 15°C           | 0.890 |
| Kinematic Viscosity @ 100°C (cSt) | 13.9  |
| Kinematic Viscosity @ 40°C (cSt)  | 125.0 |
| Viscosity Index                   | 109   |
| Flash Point COC (°C)              | 230   |
| Pour Point (°C)                   | -18   |
| TBN (mg KOH/g)                    | 6.55  |
| Sulphated Ash (% wt)              | 0.80  |