



Autotrans LVA

Fully synthetic automatic transmission fluid

Product code: A050

Product Description:

Autotrans LVA is a premium quality multi-vehicle automatic transmission fluid developed for use in a wide range of passenger car applications.

Autotrans LVA is formulated using the highest quality fully synthetic base stocks together with advanced additive technology which combine to provide a low viscosity fluid with significant fuel saving benefits.

Benefits:

- Extended fluid life
- Exceptional oxidation resistance
- Proven anti-wear performance
- Fuel saving benefits
- Excellent sludge and varnish control
- Optimised frictional characteristics
- Outstanding low temperature fluidity

Applications:

Autotrans LVA is an ideal choice for use in many of the latest passenger car automatic transmissions, including 7, 8 & 9 speed units produced by ZF and modern Mercedes-Benz auto transmissions.

Typical Test Data:

Appearance	Green fluid
Density @ 15°C	0.845
Kinematic Viscosity @ 100°C (cSt)	6.00
Kinematic Viscosity @ 40°C (cSt)	29.5
Brookfield Viscosity @ -40°C (cP)	12,090
Flash Point COC (°C)	225
Pour Point (°C)	-45



TECHNICAL DATA SHEET

Product Specification:

Aisin Warner	AW-1, JWS 3324
Audi/VW	TL 052 162-Z (G 060 162) G 055 005 G 055 162 G 055 540 G 052 540
Bentley	JNV 862 564 D
BMW	83 22 0 142 516 83 22 2 152 426 83 22 2 305 397 (ATF 3) 83 22 2 289 720 (ATF 3+)
DSIH	6p805 (Geely, Ssangyong, Mahindra 6sp)
Fiat	9.55550-AV5
GM	Dexron HP
Honda	DW-1, Honda Type 3.0
Hyundai/Kia	SP-IV, SPH-IV, SP-IV RR, NWS-9638
Jaguar	JDE26444
JASO	1-A-LV
Mazda	ATF FZ
Mitsubishi	ATF-J3, ATF-PA, SP-IV
Nissan	Matic S, Matic W
Toyota	WS (JWS 3324)
Mercedes-Benz	236.12, 236.14, 236.15, 236.16, 236.17, 236.41
Saab	93 165 147
Volvo	6 Speed MY 2011-2013 (P/N31256774 or 31256675)
ZF	6 Speed (S671 090 255) Lifeguard Fluid 8 TE-ML 11

- Autotrans LVA is recommended for Dexron IIIH applications out of warranty.