

# TECHNICAL DATA SHEET

## HD Adhesive Grease

#### **EXOL LUBRICANTS LIMITED**

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720 WWW.EXOL-LUBRICANTS.COM



### TECHNICAL DATA SHEET

### **HD Adhesive Grease**

Semi synthetic waterproof grease. Product code: Z026

#### Product Description:

HD Adhesive Grease is a premium quality semi-synthetic waterproof extreme pressure grease. It is designed specifically for slow to medium speed plain and antifriction bearing applications in marine and other hostile environments.

#### **Benefits:**

- Waterproof in both salt and fresh water.
- Excellent sealing properties to resist ingress of dirt and moisture
- Good load carrying capability reducing friction and wear
- Highly adhesive to resist vibration and shock
- Exceptional corrosion resistance

Appearance	Smooth adhesive grease
Colour	Green
NLGI classification	2
Thickener	Lithium soap
Base oil	Semi-synthetic
Base oil viscosity @ 40°C (cSt) (IP 71)	1000
Worked penetration (IP 50)	265-295
Dropping point (IP 132)	185 min
Oil separation (IP 121)	5 max
Copper corrosion (IP 112)	Pass
Resistance to corrosion EMCOR (IP 220)	0:0
Water washout (ASTM D1264) @ 39°C	2.5
Four ball weld load (IP 239) Kg	260
Timken OK load (IP 326) Kg / Ib	20 (45)
Operating temperature range	-7°C to +140°C

#### **Typical Test Data:**





#### Application:

HD Adhesive Grease is widely used in the water utilities industry and as a wheel bearing grease for boat trailers and other marine applications.

HD Adhesive Grease can be applied manually or by using a standard grease gun (400g cartridges are available). As with all greases used for the first time check compatibility with the grease applied previously, and if necessary purge the bearings prior to application. Take extra care not to over lubricate.

#### Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.